Declaration of Performance

No. CZ0002-018 (eng)

1 Unique identification code of the product-type

Orstech DP 100, Orstech DP 100 ALU

TECH Wired Mat MT 5.1, TECH Wired Mat MT 5.1 Alu1

Thermal Insulation of Building Equipment and Industrial Installations (ThIBEII)

> Saint - Gobain Construction Product CZ a.s. Smrčkova 2485/4, 180 00 Prague 8 - Libeň Czech Republic IČO: 25029673, DIČ: CZ 25029673

> > Institut pro testování a certifikaci a.s.

EN 14303:2009 + A1:2013

| 4 | Authorised representative: | not relevant |
|---|----------------------------|----------------------|
| 5 | Systém/s of AVCP: | System 1 System 3 |

1023

6 Notified body/ies:

Manufacturer:

Product/s:

Intended use or uses:

2

3

Harmonised standard:

| Essential characteristics | Performance | | | Abreviation | | Unit | | Declared performance/s: | | |
|--|--|-------------------------------|-------|-------------|----------------|-------------------|--------|----------------------------|--------|-------|
| Reaction to fire | Reaction to fire | | | RtF | | Euroclass | | A1 | | |
| Acoustic absorption index | Sound absorption | | | | - | | - | | NPD | |
| | Thermal resistance | Т°С | 50 °C | 100 °C | 200 °C | 300 °C | 400 °C | 500 °C | 600 °C | 660°C |
| Thermal resistance | | [∆] D (W/m*K) | 0,041 | 0,047 | 0,063 | 0,084 | 0,110 | 0,143 | 0,182 | 0,209 |
| | Thickness | | | d | | mm | | 30-120 | | |
| | Tolerances | | | | Т | | | | T2 | |
| Water permeability | Water absorption | | | WS | | kg/m ² | | WS1 | | |
| Water vapour transmission | Water vapour diffusi | r vapour diffusion resistance | | | s _d | | m | | NPD | |
| Rate of release of corrosive | Trace amounts of soluble ions and pH value | | | CL | | mg/kg | | 10 | | |
| substances | Realease of Dangerous Substances | | | | - | | - | | NPD | |
| Continous glowing combustion | tinous glowing combustion Continous glowing combustion | | | | - | | - | | NPD | |
| Durability of against reaction to fire ageing/degradation | Durability Characteristics | | | RtF | | Euroclass | | A1 | | |
| Durability of reaction to fire against ageing/degradation and against high temperature | Durability Characteristics | | | | - | | - | | NPD | |
| Durability of thermal resistance against ageing/degradation and against high temperature | Maximum Service Temperature | | | | ST(+) | | °C | | 660 | |
| | Dimensions and tolerances | | | | Т | | - | | T2 | |
| Durability of thermal resistance against heat, weathering, | Dimensional stability, or | | | | DS(TH) | | - | | NPD | |
| ageing/degradation | Maximum Service Temperature | | | | ST(+) | | °C | | 660 | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued by the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jiří Šulák *Name* Plant director *Function*



1.9.2023 *Date* Častolovice *Place*



101 03